

Section VIII

Specifications

Dimmer Bank

	2.4 KW	6 KW
Weight	85 lb. <i>(38kg)</i>	220 lb. <i>(98kg)</i>
Dimensions		
Height	19 in. <i>(48cm)</i>	25 in. <i>(62.5cm)</i>
Depth	10 in. <i>(25cm)</i>	12 in. <i>(31cm)</i>
Width	30 in. <i>(75cm)</i>	41 in. <i>(104cm)</i>
Electrical Input		
Nominal Voltage	120 vac	120 vac
Voltage Range	100-140 vac	100-140 vac
Control Voltage	0-10 vdc	0-10 vdc
120/208 vac 3 Phase / 4 wire 50-60 hz	60A / phase	150A / phase
120/240 vac 1 phase 2 wire	100A / Line leg	250A / Line leg
Output		
Current	20A / Dimmer	50A / Dimmer
Power	2.4 KW / Dimmer 21.6 KW / System	6KW / Dimmer 54KW / System
Minimum Load	10w	10w
Losses		
No Load	8 watt	8 watt
Full Load	60 watt	120 watt

Control Console

	9 - Channel	18 - Channel
Weight	15 lb <i>(6.6kg)</i>	20 lb <i>(9kg)</i>
Dimensions		
Height	6 in. <i>(152mm)</i>	6 in. <i>(152mm)</i>
Depth	13 in.. <i>(330mm)</i>	13 in. <i>(330mm)</i>

Width	17.5 in. (455mm)	25.5 in. (648mm)
Electrical Input	24vac 1a 50-60hz	24vac 1a 50-60hz
Electrical Output	0-10vdc, 50ma / channel	0-10vdc, 50ma / channel

www.klieglbros.com